

"Custom Solutions for your Application"

E-PAK FEED-THRU PACKER ESP2355





Adding Value to Your ESP Completion

The E-Pak Packer has been specifically designed to protect the investment in your wellbore. Protection of your up-hole casing is critical to the longevity of your well, even when running an ESP in tight casing.

The E-pak combines best-in-class anchoring, sealing, and feed-thru technologies to give you the capability to protect your casing while maintaining a fully-open tubing ID that allows standard well control techniques to be applied, when necessary.

Advantages

- ID fully open to tubing drift
- Hydraulic set (no pipe manipulation)
- Straight pull release
- 4 feed-thru bypasses
- Cost-effective redress

Specifications

Casing Size:5 1/2" 20-23 lbs/ftTop Connection:2 3/8" API EUE 8rd BoxBottom Connection:2 3/8" API EUE 8rd Box

Tensile Rating: 70,000 lbs
Shear Release (Straight Pull): 30,000 lbs
Pressure Rating (above): 5,000 psi
Temperature Rating: 310°F

Max OD: 4.500" (4.645" for 15.5-17#)

 Tubing ID:
 1.930"

 Feed-Thru ID:
 1/2" (4 places)

Length: 45.5" (without pup joints)

Setting Pressure: 3,000 psi